



FEASA™ OPTICAL HEAD

LED INTENSITY TESTING

THE ULTIMATE SOLUTION TO LED INTENSITY ISSUES



OH-2 Optical Head



OH-3 Optical Head



OH-4 Optical Head

Discrepancies in Intensity Testing are often caused by variations in the placement of LEDs on PCBs. The Feasa Optical Head's were specifically designed to address these issues.

When stability of Intensity testing is important to you The Feasa Optical Head in conjunction with the Feasa LED Analyser delivers a complete Testing Solution.

The Feasa Optical Head OH-4 is an ideal solution for testing right angled LED's

Features:

- Compensation for LED Placement
- Robust / Compact Design
- Economical and Easy To Use
- Repeatable Intensity Readings
- Reduced sensitivity to ambient light
- Fast Worldwide Delivery

Specifications:

Part No: Feasa OH-2
 Dimensions: Outer Diameter 4.55mm
 Length: 25mm
 Test LED's on 5mm centre to centre
 Mounting Hole Size 4.6mm

Part No: Feasa OH-3
 Dimensions: Outer Diameter 4.55mm
 Length: 49.5mm
 Test LED's on 5mm centre to centre
 Mounting Hole Size 4.6mm

Part No: Feasa OH-4
 Dimensions: Outer Diameter 4.55mm
 Length: 58.1mm
 Test LED's on 5mm centre to centre
 Mounting Hole Size 4.6mm

Ordering Information:

Feasa Optical Head (Vertical Access)
 Feasa Optical Head (Vertical Access)
 Feasa Optical Head (Side Access)

Part No.: OH-2
 Part No.: OH-3
 Part No.: OH-4

